



5000 NON TURBO-ANTIQUUE

Tractor must be stock appearing

- No stretched hood to allow larger engine

- No aluminum rims

- No aluminum custom wide front ends

Drawbar to be 20" high + 18" from center to rear axle.

- Must be rigid in all directions.

- Hook point of "D" style 3" to 4" opening

Wheelie bars required

- 10" from ground + reach behind rear tires

- Wheelie bar needs to be rigid

Any safety equipment allowed

- Side shields

- Kill switch or air shutoff for diesels

- Scatter blanket

Tire size (#5000 class only)

- 14.9 -38 15.5-38 or 229 square inch footprint

- Cut tires of any cut allowed

Custom weight bars (aluminum allowed)

Front no more than 24" from the foremost point of tractor

Rear weight bars + Weights not to be behind tires

Rear weights can't hinder hook up to sled

R.P.M. (to be no more than)

A. 3000 6 cylinder

B. 2500 4 cylinder

C. 2000 2 cylinder

Race gas, Diesel, Propane or regular gas

No alcohol, NOS

Engines

A. Only 1 up draft carb for make + model

B. No custom intake to accommodate a larger up or side draft carb.

C. Only 1 LP regulator

D. Stock diesel pump for make + model (no turbo)

E. Exhaust to go through original hole at factory position in hood.

F. No truck motors

G. No HD 800 mm motors

H. 310 engine is allowed 1800, 1850, etc., must use the original style differential, transmission and sheet metal.

[\(Click return arrow to return to Main Rules page\)](#)