

## 6200 ALTERED STREET CLASS RULES

1. 505 CUBIC INCH LIMIT IS ALLOWED WITH 2% TOLERANCE ( **515 LIMIT** ).
2. NO AFTERMARKET BLOCKS ALLOWED.
3. UPRIGHT HEADERS PERMITTED.
4. FACTORY PRODUCTION IRON CYLINDER HEADS MUST BE USED, WITH EXEMPTION OF SCJ ALUMINUM CYLINDER HEAD AND THE GM BOWTIE ALUMINUM CYLINDER HEAD. (**NO PRO-STOCK STYLE HEADS**)  
**EXAMPLE:** FORD C-460, BLUE THUNDER THOR, BOSS HEMI.... CHEVY: BIG CHIEF, BIG DUKE..... DODGE: PREDATOR, HEMI....
5. MUST USE 4150 STYLE CARBURETOR. ( **EXEMPTION SMALL BLOCK TRUCKS** ).
6. NO BLOWERS OR SUPER CHARGERS ALLOWED.
7. DOT APPROVED TIRES ONLY. NO CUTTING OR GROOVING OF TIRES.
8. NO TIRE TALLER THAN 35" PERMITTED.
9. TRANSMISSION:
  - A. MANUAL TRANSMISSIONS: MUST USE A BLOW PROOF BELL HOUSING.
  - B. AUTOMATIC TRANSMISSIONS: MUST HAVE SFI APPROVED FLEX PLATE SHIELD AND BLANKET AROUND CLUTCHING COMPONENTS.
10. HANGING WEIGHTS ALLOWED
11. WEIGHTS MUST BE ATLEAST 10" OFF GROUND. ( 1" TOLERANCE )
12. 60" MAX FROM CENTER OF FRONT AXLE HOUSING. ( 1" TOLERANCE )
13. 80" WIDE MAX OR 40" FROM CENTER OF TRUCK. ( 1" TOLERANCE )
14. TOW HOOK ON FRONT REQUIRED WITH NO SHARP EDGES.
15. DRIVE TRAIN MUST BE FACTORY PRODUCTION 1 TON OR LESS. NO DROP BOX OR REVERSER ALLOWED.
16. ALL PULLING VEHICLES MUST HAVE KILL SWITCH TO KILL IGNITION. MUST BE AT LEAST 30" OFF THE GROUND AND WITHIN 6" OF CENTER OF TRUCK.
17. HOMEMADE HITCHES PERMITTED. ALL HITCHES MUST BE SAFE, SECURE, AND RIGID IN ALL 4 DIRECTIONS. NO HYDRAULIC HITCHES PERMITTED.
18. HITCH HEIGHT MAX 24"
19. HITCHES MUST BE ATLEAST 36% OF WHEELBASE FROM CENTER OF REAR AXLE TO THE HOOK POINT.
20. HITCH MOUNTING POINT CANNOT BE FORWARD OF THE CENTER OF THE REAR AXLE, AND NO MORE THAT 2" ABOVE FRAME RAIL. ( ATTACHMENT POINT )
21. DRIVE LINE NEEDS TO HAVE LOOPS AROUND U-JOINTS. THEY MUST EXTEND ½" PAST U-JOINT ON BOTH SIDES AND MINIMUM OF 3/16" THICK.
22. MUST HAVE A MINIMUM OF 2 LEAF SPRINGS IN REAR ATTACHED TO HOUSING IN FACTORY LOCATION.
23. LADDER BARS ARE PERMITTED. ( FRONT AND REAR )
24. SOLID SUSPENSION IS PERMITTED.
25. HYDRAULIC STEERING PERMITTED.
26. CARBURETORS MUST NOT BE FORWARD OF THE CENTER OF FRONT AXLE.
27. ALL FACTORY GLASS MUST BE PRESENT.
28. ALL TRUCKS MUST HAVE STOCK SHEET METAL PRESENT ( EXCEPT HOOD AND TAILGATE).
29. BED FLOOR CAN BE REMOVED, BUT MUST HAVE A BED COVER OR BED LINER IN PLACE.
30. ALL HOODS MUST BE ABLE TO OPEN COMPLETELY WITHOUT INTERFERENCE OF AIR CLEANER OR ANY OTHER OPSTRUCTION.
31. PUMP GAS OR RACE GAS ONLY. **NO NITROUS, NITROUS ACCESORIES OR ALCOHOL ALLOWED**
32. ALL BODY PARTS MUST REMAIN INSIDE VEHICLE AT ALL TIMES WHILE GOING DOWN TRACK.

33. IF YOUR TRUCK MEETS THE RULES FOR THE SMALL BLOCK CLASS OR THE HOT STREET CLASS YOU ARE LEGAL TO PARTICIPATE IN THE ALTERED CLASS.
34. HELMET AND RACING JACKET REQUIRED.
35. FIRE EXTENGUISHER REQUIRED INSIDE TRUCK ( EASILY ACCESSIBLE).

**CLASS PAYOUT:**

**1<sup>ST</sup> - \$120**

**2<sup>ND</sup> - \$80**

**3<sup>RD</sup> - \$60**

**4<sup>TH</sup> - \$40**