

6200 SMALL BLOCK FWD

WEIGHT: 6200 LBS WITH 50 LB TOLERANCE

ENGINE:

1. ENGINE MUST BE CLASSIFIED AS A SMALL BLOCK FROM FACTORY. AFTERMARKET BLOCKS ALLOWED, WITH THE EXCEPTION OF THE FORD CLEVELAND STYLE MOTOR. (CLEVELAND STYLE MOTOR MUST RUN A FACTORY PRODUCTION STYLE BLOCK THAT WAS AVAILABLE IN A PRODUCTION CAR OR TRUCK AND HAVE ORIGINAL CASTING NUMBERS IN PLACE). NO FORD MODULAR STYLE ENGINE. NO CRYSLER HEMI STYLE ENGINE ALLOWED.
2. LS ENGINES PERMITTED. MUST BE FACTORY BLOCK AND FACTORY HEADS. MUST HAVE ORIGINAL CASTING NUMBERS IN PLACE.
3. 440 CUBIC INCH LIMIT WITH A 1% TOLERANCE.
4. ENGINE MUST BE IN FACTORY LOCATION. RADIATOR MUST BE LOCATED IN FRONT OF ENGINE IN STOCK LOCATION.
5. NO DRY SUMP OILING SYSTEM ALLOWED.
6. CYLINDER HEADS MUST BE FACTORY VALVE ANGLE. HEADS MAY BE ALUMINUM OR CAST IRON. HEADS MUST ACCEPT A CAST INTAKE THAT IS READILY AVAILABLE TO THE PUBLIC. NO SHEET METAL INTAKES ALLOWED.
7. NO RAISED RUNNER HEADS ALLOWED.
8. ONLY ONE CARBURETOR ALLOWED AND IT MAY BE 4150 OR 4500 FLANGE. FUEL MAY BE PUMP GAS OR RACE FUEL. OXYGENATED FUEL ALLOWED. FUEL INJECTION ALLOWED. NO ALCOHOL, NITROUS OXIDE, OR NITROUS ACCESSORIES ALLOWED ON ENGINE. (PLATE, ECT.).

CHASSIS

1. ANY DOT APPROVED TIRE WILL BE ALLOWED NOT TO EXCEED 35X14.50 SIZE. NO CUTTING OR GROOVING OF TIRES ALLOWED.
2. MUST BE 1 TON OR LOWER DRIVE TRAIN.
3. DRIVE SHAFT LOOPS AND UNIVERSAL SHIELDS REQUIRED.
4. BLOWPROOF BELL HOUSING REQUIRED FOR MANUAL TRANSMISSION. A BLANKET OR SHIELD IS REQUIRED FOR AUTOMATIC.
5. WHEEL BASE MUST BE FACTORY SPECIFIC FOR YEAR AND MAKE. NO ALTERED WHEEL BASES ALLOWED.
6. TRUCKS WILL BE LIMITED TO AN EXTENDED CAB WITH SHORT BED. WHEEL BASE LIMIT OF 144".

7. NO FIBERGLASS BODY PARTS WITH THE EXCEPTION OF HOOD AND TAILGATE.
8. ALL HITCHES MUST BE SAFE, SECURE, AND RIGID IN ALL DIRECTIONS. MAX HEIGHT OF 24". NO HYDRAULIC HITCHED ALLOWED. HITCHES MUST BE ATLEAST 36" OF WHEEL BASE. HITCH WILL BE MEASURED FROM CENTER OF REAR AXLE TO THE HOOK POINT ON HITCH. 1" ALLOWANCE ON ALL MEASUREMENTS.
9. HANGING WEIGHTS WILL BE ALLOWED. WEIGHT CAN NOT BE MORE THAT 60" FROM THE CENTER OF FRONT AXLE TO THE FURTHER MOST POINT OF WEIGHT. 1" ALLOWANCE ON MEASUREMENTS.
10. ANY LOSS OF WEIGHTS, EXCESSIVE FLUID, PARTS, ETC. WILL BE GROUNDS FOR DISQUALIFICATION. EXEMPTION IF FORWARD MOTION HAS STOPPED WHEN BREAKAGE OCCURS.
11. IF PULLER GOES OUT OF BOUNDS THAT VEHICLE WILL BE DISQUALIFIED.
12. PULLER WILL BE ALLOWED A SECOND ATTEMP TO START THE SLED IF THE PULLING VEHICLE GIVES UP ON ATTEMP BEFORE 75 FT MARK. (VEHICLE CAN GO FURTHER THAN 75 FT BUT MUST BE TRYING TO STOP) (UNLESS IN PULLOFF)
13. A FULL PULL IS 320 FT. ANYTHING PAST THAT WILL REQUIRE A PULL OFF UNLESS STATED OTHERWISE BY PROMOTER.
14. ANY INTERFERENCE FROM DRIVER, CREW ON TRACK, OR SCALES IS GROUNDS FOR DISQUALIFICATON.

SAFETY

1. **ALL DRIVERS MUST WEAR A HELMET, AND APPROVED FIRE JACKET.**
2. **EVERY PULLING VEHICLE MUST BE EQUIPPED WITH AT LEAST A 5 LB FIRE EXTINGUISHER.**
3. **VEHICLE MUST HAVE A WORKING KILL SWITCH WITH A 1" HOLE FOR HOOK POINT AT THE REAR OF TRUCK. MUST BE WITHIN 3 " OF CENTER OF TRUCK.**

PAYOUT

1ST - \$120.00

2ND - \$ 80.00

3RD - \$ 60.00

4TH - \$ 40.00